



## SRM-15.6 Series 15.6" Sunlight Readable LCD Monitor

- Produces Clear, Sharp Images Even in Direct Bright Sunlight
- 1,000 or 1,500 nits Brightness
- **TRU-Tuff** Ensures Maximum Shock & Vibration Resistance
- Lockable On-Screen Display Controls
- Dim-to-Black Via Front Pushbuttons
- Auto Re-Start After Power Loss
- Optical Bonding Available
- 3 Year Warranty


The SRM-15.6 Sunlight Readable monitors are designed to operate in direct bright sunlight, or in other high ambient-light conditions. They utilize state-of-the-art LED backlights to produce over 1,000 nits of brightness (vs. 250-300 nits for standard monitors). This results in amazingly bright, crystal-clear images, even with direct, bright sunlight on the face of the screen. The SRM-15.6 Sunlight Readable monitors are ideal for use in a wide range of industrial, law enforcement, aviation, marine, military, inspection, advertising, material handling (cranes) and transportation applications where viewability in direct bright sunlight is crucial.

Specifications					
MODEL	SRM-15.6J	SRM-15.6U	SRMXOB-15.6G-24	SRMX-15.6R-24	SRMHX-15.6Z
LCD Panel	15.6" Color LCD; LED Backlights				
Resolution	1366 x 768 (WXGA) Accepts Inputs up to 1920 x 1080		1920 x 1080 (Full HD)		
Viewable Area	13.55" (W) x 7.62" (H) (344.23 x 193.53 mm)				
Pixel Pitch	0.252mm		0.179mm		
Display Colors	16.2 M				
Aspect Ratio	16:9				
Brightness	1,000 nits				1,500 nits
Optical Bonding	Optional		Standard	Optional	
Contrast Ratio	500:1		700:1		
Viewing Angle	170° (H) x 160° (V)			140° (H) x 120° (V)	160° (H) x 140° (V)
Response Time	8msec Trf				
Control	OSD (On-Screen Display) via Front Panel Pushbuttons				
Video Inputs	DVI, Composite BNC Loop-Thru (Includes VGA & HDMI Adapters)	VGA, HDMI Composite (BNC Loop-Thru)	DVI, HDMI, DisplayPort	VGA, HDMI DisplayPort	VGA, HD-SDI, HDMI, Composite (BNC Loop-Thru)
Audio	Front Speakers	Rear Speakers	Optional		
Mirror & Zoom	---		Standard		---
Power Requirement	12-24 VDC (2.5mm Barrel Plug with Locking Connector)		12-24 VDC	12-24 VDC (2.5mm Locking Connector)	12-24VDC/90-240VAC
Power Consumption	25 Watts				
Enclosure	Powder-Coated Steel				
Mounting	100 x 100 Rear VESA Mount Holes				
Operating Temp.	+32° to 140° F (0° to +60° C)		14° to 158° F (-10° to +70° C)		
Humidity	5-90% RH				
Shock	50 G (20 msec. 1/2 sine)				
Vibration	1.5G RMS 10-200 HZ				
Dimensions	15.0" (W) x 10.2" (H) x 2.0" (D) (381.0 x 259.08 x 50.80mm)		14.52" (W) x 9.74" (H) x 1.57" (D) (368.8 x 247.4 x 40mm)		
Weight	7.39 lbs. (3.35 kg)		5.69 lbs. (2.5 kg)		
Warranty	3 Years				

## SRM-15.6 Series

### 15.6" Sunlight Readable LCD

Dimensions (Except for Full HD Model):



### Standard Accessories:

- VGA Cable
- DVI-to-HDMI Cable (J model only)
- DVI-to-VGA Adapter (J model only)
- Power Pigtail with Locking Connector
- HDMI Cable (G, U, R & Z models)

### Available Options:

- -30° to +80°C Operating Temperature (SRM-15.4C)
- Stainless Steel NEMA 4X Waterproof Enclosure (SRMXW-15.6R-24)
- Optical Bonding (SRMXOB-15.6G-24)
- 90-240VAC External Power Adapter (PS-12-LC)
- Automated Ambient Light Sensor
- Protective Anti-Reflective Glass
- Speakers
- Tabletop Base (TTB-21)
- Wall Mount Bracket