



VMTRWP-15 Series

15" Panel-Mount Waterproof Touch Screen Monitor

- 5-Wire Resistive Touch Screen
- Steel or Stainless Steel Panel-Mount Enclosure
- Waterproof NEMA 4X/IP 65 Front Face
- Video Inputs: VGA, DVI-D, HDMI and DisplayPort
- Lockable On-Screen Display (OSD) Controls
- Auto Re-Start After Power Loss
- **TRU-Tuff** Ensures Maximum Shock/Vibration Resistance
- 3-Year Warranty

The VMTRWP-15 Series 15" industrial-grade touch screen monitors feature rugged NEMA 4X waterproof stainless steel panel-mount enclosures. The 5-wire resistive touch screen can be activated by almost any object—gloved finger, stylus, pen, etc. They are ideal for wash-down environments in manufacturing plants, food processing or any other areas where liquids, steam or moisture may damage standard monitors. An extensive list of OEM options enables you to customize the VMTRWP-15 Series monitors to meet your exact needs.

All TRU-Vu industrial LCD monitors are specifically designed for use in demanding applications. Every TRU-Vu monitor utilizes industrial-grade components and high-end LCD panels not found in retail/consumer-grade monitors. This ensures superior image quality, improved performance and greater durability. Our 3-Year Warranty ensures you of reliable worry-free operation. Visit www.TRU-VuMonitors.com for more details.

Specifications		
MODEL	VMTRWP-15C-24-SS	VMTRWP-15R-24
LCD Panel	15" Color TN LCD Panel (LED Backlights)	
Touch Technology	5-Wire Resistive Touch	
Touch Interface	USB	
Resolution	1024 x 768 (XGA)	
Viewable Area	11.97" (W) x 8.98" (H) (304.12 x 228.09 mm)	
Pixel Pitch	0.297mm	
Display Colors	16.2 M	
Aspect Ratio	4:3	
Brightness	350 nits	
Contrast Ratio	700:1	
Response Time	8 msec Trf	
Viewing Angle	160° (H) x 150° (W)	
Control	OSD (On-Screen Display) via Rear Panel Pushbuttons	
Video Inputs	VGA, DVI-D	VGA, HDMI, DisplayPort
Power Requirement	12-24VDC (2.5mm Barrel Plug)	
Enclosure	Waterproof Stainless Steel Panel-Mount (Rear Clamp)	Steel Panel-Mount (Rear Clamp)
Rating	NEMA 4X / IP65	
Operating Temperature	32° to 149° F (0 to 65° C)	
Humidity	8-90%RH	
Shock	50 G (20 msec, ½ sine)	
Vibration	1.5G RMS 10-200 HZ	
Dimensions	15.98" (W) x 12.39" (H) (405.80 x 314.60 mm)	
Warranty	3 Years	