



### VMTW-15 Series 15" Waterproof Industrial Touch Screen Monitor

- 5-Wire Resistive Touch
- NEMA 4X Waterproof Stainless Steel Enclosure
- Video Inputs: VGA, DVI-D
- Lockable On-Screen Display (OSD) Controls
- Auto Re-Start After Power Loss
- **TRU-Tuff** Ensures Maximum Shock/Vibration Resistance
- 3 Year Warranty

The VMTRW-15C-24 15" Industrial-Grade touch screen monitors feature rugged NEMA 4X waterproof stainless steel enclosures. The 5-wire resistive touch screen can be activated by almost any object – gloved finger, stylus, pen, etc. They are ideal for wash-down environments in manufacturing plants, food processing or any other areas where liquids, steam or moisture may damage standard monitors. An extensive list of OEM options enables you to customize the VMTRW-15C-24 monitors to meet your exact needs.

All TRU-Vu industrial LCD monitors are specifically designed for use in demanding applications. Every TRU-Vu monitor utilizes industrial-grade components and high-end LCD panels not found in retail/consumer-grade monitors. This ensures superior image quality, improved performance and greater durability. Our 3-Year Warranty ensures you of reliable worry-free operation. Visit [www.TRU-VuMonitors.com](http://www.TRU-VuMonitors.com) for more details.

	Specifications
<b>MODEL</b>	<b>VMTRW-15C-24</b>
<b>LCD Panel</b>	15" Color LCD; LED Backlights
<b>Touch Screen Type</b>	5-Wire Resistive Touch
<b>Touch Screen Interface</b>	USB
<b>Resolution</b>	1024 x 768 (XGA)
<b>Viewable Area</b>	11.97 (W) x 8.98 (H) (304.128 x 228.096) mm)
<b>Pixel Pitch</b>	0.297 mm
<b>Display Colors</b>	16.7M
<b>Aspect Ratio</b>	4:3
<b>Brightness</b>	350 nits
<b>Contrast Ratio</b>	700:1
<b>Viewing Angle</b>	160° (H) x 150° (V)
<b>Response Time</b>	8 msec
<b>Control</b>	OSD (On-Screen Display) via Rear Panel Pushbuttons
<b>Video Inputs</b>	VGA & DVI
<b>Power Requirement</b>	12-24 VDC
<b>Enclosure</b>	Stainless Steel
<b>Enclosure Rating</b>	NEMA 4X Waterproof
<b>Mounting</b>	100 x 100 mm Rear VESA Mount Holes
<b>Operating Temperature</b>	+32° to +149° F (0° to +65° C)
<b>Humidity</b>	5-90% RH
<b>Shock</b>	50 G (20 msec, 1/2 sine)
<b>Vibration</b>	1.5 G (10-200 Hz P-P)
<b>Dimensions</b>	TBD
<b>Included Accessories</b>	DVI Cable, VGA Cable, Power Pigtail

Specifications subject to change without notice.