



VMT-21.5 Series 21.5" Touch Screen Monitor

- Full HD Resolution: 1920 x 1080 (1080p/60)
- SAW or 5-Wire Resistive Touch or Capacitive
- Video Inputs: VGA, HDMI, DVI, Composite (BNC)
- Internal Speakers
- Lockable On-Screen Display Controls
- Can Be Customized To Meet Your Needs
- Auto Re-Start After Power Loss
- 3-Year Warranty

The VMTS-21.5D SAW Touch Screen monitors are designed for maximum light transmission and superb optical clarity. They have a very durable glass surface, with the highest level of scratch-resistance of any touch technology. The VMTS-21.5D SAW Touch Screens are ideal for use in a wide range of military, industrial, law enforcement, aviation, marine, inspection, advertising and transportation applications.

The VMTR-21.5R is a 5-Wire Resistive Touch Screen. This model can be activated with nearly any type of device: exposed finger, glove, stylus, pointer, etc. Its immunity to surface contaminants (oil, water, dirt) makes it a popular choice for more challenging environments. It is a very cost-effective choice for public access, kiosks and more.

Specifications			
MODEL	VMTS-21.5R	VMTR-21.5R	VMTC-21.5V
LCD Panel	21.5" Color LCD; LED Backlights		
Touch Technology	SAW (Surface Acoustic Wave)	5-Wire Resistive	Capacitive
Touch Interface	USB		
Display Resolution	1920 x 1080 (1080p/60 Full HD)		
Viewable Area	18.76" x 10.55" (476.6 x 268.1 mm)		
Pixel Pitch	0.248mm		
Display Colors	16.7 M		
Aspect Ratio	16:9		
Brightness	250 nits		
Contrast Ratio	3,000:1		
Viewing Angle	178° (H) x 178° (V)		
Response Time	25 ms Trf		
Control	OSD (On-Screen Display) via Pushbuttons		
Video Input Connectors	VGA, HDMI & DisplayPort		VGA
Video Inputs	VGA, HDMI, Composite BNC Input, Composite BNC Output		
Power Requirement	90-260 VAC	12 VDC/90-240 VAC	
Power Consumption	25W		
Enclosure	Powder-Coated Steel	ABS	
Mounting	Included Base or 100 x 100 mm Rear VESA Mount Holes		
Operating Temperature/Humidity	32° to 140°F (0° to +60°C); 5-90% Non-Condensing		
Shock	50G, Half-sine Wave, 20ms, X/Y/Z		
Vibration	Acceleration: 1.5 G RMS; Random Wave; 10-200Hz; 30 mins Per Axis (X,Y,Z)		
Dimensions	20.87" W x 12.68" H x 2.17" D (530.5 x 322 x 55mm)	20.68" W x 12.60" H x 2.18" D (525.3 x 320 x 55.4mm)	
Weight	13.6 lbs. (6.2 Kg)	9.8 lbs. (4.5 Kg)	
Included Accessories	VGA and HDMI Cables	VGA Cables	
Warranty	3-Years		