

SRMW-24R-SS

24" Waterproof Sunlight Readable HD LCD Monitor



- True Sunlight-Readable HD Monitor
- 1,000 Nits Brightness
- Waterproof NEMA 4X Stainless Steel Enclosure
- Full HD Resolution: 1920 x 1080 (1080p/60)
- LED Backlights
- Auto Re-Start After Power Loss
- Protective Anti-Reflective Glass
- Can Be Customized To Meet Your Needs
- 3-Year Warranty

The SRMW-24R-SS Sunlight Readable HD LCD monitors are designed to operate in direct bright sunlight, or in other high ambient-light conditions. These state-of-the-art monitors produce 1,000 nits of brightness (vs. 150-200 nits for standard laptops). This results in amazingly bright, crystal-clear HD images, even with direct, bright sunlight on the face of the screen. The NEMA 4X fully waterproof enclosure ensures that the monitor will withstand rain, snow, seawater, etc. The SRMW-24R-SS Sunlight Readable monitors are ideal for use in a wide range of industrial, law enforcement, aviation, marine, military, inspection, advertising and transportation applications where view-ability in direct bright sunlight is crucial.


All TRU-Vu industrial LCD monitors are specifically designed for use in demanding applications. Every TRU-Vu monitor utilizes industrial-grade components and high-end LCD panels not found in retail/consumer-grade monitors. This ensures superior image quality, improved performance and greater durability. Our 3-Year Warranty ensures you of reliable worry-free operation. Visit www.TRU-VuMonitors.com for more details.

	Specifications
MODEL	SRMW-24R-SS
LCD Panel	24" Color; LED Backlights
Display Resolution	1920 x 1080
Viewable Area	20.92" x 11.76" (531.4 x 298.9 mm)
Pixel Pitch	0.277mm
Display Colors	16:7 M
Aspect Ratio	16:9
Brightness	1,000 nits
Contrast Ratio	5,000:1
Viewing Angle	178° (H) x 178° (V)
Response Time	25 msec
Control	OSD (On-Screen Display) via Rear Pushbuttons
Video Input Connectors	VGA, HDMI, DisplayPort
Power Requirement	90-240 VAC
Power Consumption	45W
Enclosure	Stainless Steel, NEMA 4X
Mounting	100 x 100mm Rear VESA Mount Holes
Operating Temperature	-4° to 158° F (-20° to +70° C)
Humidity	5-90% RH
Shock	50G Half-sine
Vibration	1.5G RMS 10-200Hz
Dimensions	24.01" (W) x 14.31" (H) x 3.11" (D) (610 x 363.6 x 79mm)
Weight	23.44 lbs. (10.63 kg)
Warranty	3-Years

SRMW-24R-SS

24" Waterproof Sunlight Readable HD LCD Monitor

Dimensions: (mm)



Standard Accessories:

- VGA Cable
- HDMI Cable

Available Options:

- Automated Ambient Light Sensor
- 24 VDC Operation
- DVI Video Input
- Private Label
- Wall Mount Bracket
- Other Customer - Specific Modifications