



SRMZBTP-27R Series 27" High-Bright Touch Screen Monitor

- 1,000 Nits Brightness
- Full HD Resolution: 1920 x 1080 (1080p/60)
- P-Cap (Projected Capacitive) Touch Panel
- Auto Re-Start After Power Loss
- Anti-Glare Glass
- Zero-Bezel Enclosure
- Lockable On-Screen Display (OSD) Controls
- Can Be Customized To Meet Your Needs
- 3-Year Warranty

The SRMZBTP-27R High-Bright touch screen monitors are designed to operate in high ambient-light conditions. These state-of-the-art monitors produce over 1,000 nits of brightness (vs. 150-200 nits for standard laptops). This results in amazingly bright, crystal-clear HD images. The SRMZBTP-27R Sunlight Readable touch screens are ideal for use in a wide range of industrial, law enforcement, aviation, marine, military, medical, inspection, advertising and transportation applications where viewability in bright light conditions is crucial. The P-Cap touch panel enables multi-touch operation. It is compatible with all Windows and most Linux operating systems.


All TRU-Vu industrial LCD monitors are specifically designed for use in demanding applications. Every TRU-Vu monitor utilizes industrial-grade components and high-end LCD panels not found in retail/consumer-grade monitors. This ensures superior image quality, improved performance and greater durability. Our 3-Year Warranty ensures you of reliable worry-free operation. Visit www.TRU-VuMonitors.com for more details.

Specifications		
MODEL	SRMZBTP-27R-X	SRMZBTP-27R
LCD Panel	27" Color MVA LCD; LED Backlights	
Display Resolution	1920 x 1080 (1080p/60 Full HD)	
Touch Screen Type	Projected Capacitive (P-Cap)	
Touch Screen Interface	USB	
Viewable Area	23.52" x 13.25" (597.6 x 336.15 mm)	
Pixel Pitch	0.311mm	
Display Colors	16:7M	
Aspect Ratio	16:9	
Brightness	1,000 nits	
Contrast Ratio	1,000:1	
Viewing Angle	170°(H) x 160°(V)	
Response Time	5 ms Trf	
Control	OSD (On-Screen Display) via Pushbuttons	
Video Input Connectors	VGA, HDMI, DisplayPort	
Audio	Optional Dual Rear Speakers	
Power Requirement	12 VDC (2.5 mm Barrel Plug); 90-240 VAC via Included Power Brick	90-240 VAC
Power Consumption	45W	
Enclosure	ABS, with Zero-Bezel Front	
Mounting	Via Optional Base or 100 x 100 mm / 200 x 100 Rear VESA Mount Holes	
Operating Temperature	32° to 122°F (0 to 50°C)	
Dimensions	25.38" (W) x 15.25" (H) x 2.63" (D) (644.65 x 387.35 x 66.80 mm)	
Weight	16.3 lbs. (7.39 kg)	
Warranty	3-Years	

SRMZBTP-27R

27" High-Bright Touch Screen Monitor

Dimensions:



Standard Accessories:

- 90-240 VAC External Power Brick
- HDMI Cable
- USB Cable

Available Options:

- Automated Ambient Light Sensor
- Direct 90-240VAC Operation
- DVI Input
- Powder-Coated Steel Enclosure
- Dim-To-Black
- Wall Mount Brackets
- Remote Control
- Private Label
- Other Customer - Specific Modifications