



ZBMT-32 Series

32" HD Multi-Touch Touch Screen LCD Monitor

- Projected Capacitive Touch Technology
- Multi-Touch (10 Points)
- Can Be Activated Via Exposed Finger, and Surgical or Thin Cotton Gloves
- Zero-Bezel, Seamless, All Glass Front Face
- Full HD Resolution: 1920 x 1080 (1080p/60)
- Video Inputs: VGA, DVI-D, HDMI, Display Port
- Lockable On-Screen Display (OSD) Controls
- Auto Re-Start After Power Loss
- 3 Year Warranty

The ZBMT-32 Series Projected Capacitive, multi-touch, zero-bezel touch screen monitors offer the latest in LCD touch screen technology. The projected capacitive (P-Cap) touch screen can be activated via an exposed finger (like standard surface capacitive touch), and also with surgical or thin cotton gloves. The multi-touch capability allows up to 10 simultaneous inputs for selecting, zoom, flick and other functions. It is also unaffected by dirt, grease or moisture on the glass surface. The sleek all-glass, seamless, zero-bezel front face is stylish as well as functional; it is easy to clean and eliminates the potential for contamination build-up under the bezel. They are ideal for use in a wide range of healthcare, kiosk, hospitality, commercial and other applications. An extensive list of OEM options enables you to customize the ZBMT-32 Series to meet your exact needs. Compatible with all Windows and most Linux operating systems.

All TRU-Vu industrial LCD monitors are specifically designed for use in demanding applications. Every TRU-Vu monitor utilizes industrial-grade components and high-end LCD panels not found in retail/consumer-grade monitors. This ensures superior image quality, improved performance and greater durability. Our 3-Year Warranty ensures you of reliable worry-free operation. Visit www.TRU-VuMonitors.com for more details.

	Specifications	
MODEL	ZBMT-32C	ZBMT-32C-24
LCD Panel	32" Color LCD; LED Backlights	
Touch Screen Type	Projected Capacitive Touch	
Touch Interface	USB	
Display Resolution	1920 x 1080 (Full HD)	
Viewable Area	27.50" (W) x 15.47" (H) (698.4 x 392.9mm)	
Pixel Pitch	0.277mm	
Display Colors	16:7 M	
Aspect Ratio	16:9	
Brightness	400 nits	
Contrast Ratio	3,000:1	
Viewing Angle	178° (H) x 178° (V)	
Response Time	6.5 GtG	
Control	OSD (On-Screen Display) via Front Buttons	
Video Inputs	VGA, DVI	
Power Requirement	90 - 240 VAC (Optional 24VDC)	12-24 VDC
Power Consumption	TBD	
Enclosure	Powder Coated Steel	
Mounting	100 x100 mm, 100 x 200 mm Rear VESA Mount Holes	
Operating Temperature	32° to 122° F (0 to 50° C)	
Humidity	5 - 90% RH	
Shock	50G Half-sine	
Vibration	1.5G rms 10-200Hz	
Dimensions	TBD	
Weight	TBD	
Warranty	3 Years	