



### VMT-21.5 Series 21.5" Touch Screen Monitor

- Full HD Resolution: 1920 x 1080 (1080p/60)
- SAW or 5-Wire Resistive Touch
- LED Backlights
- Video Inputs: VGA, HDMI, DVI, Composite (BNC)
- Lockable On-Screen Display Controls
- Can Be Customized To Meet Your Needs
- 3 Year Warranty

The VMTS-21.5D SAW Touch Screen monitors are designed for maximum light transmission and superb optical clarity. They have a very durable glass surface, with the highest level of scratch-resistance of any touch technology. The VMTS-21.5D SAW Touch Screens are ideal for use in a wide range of military, industrial, law enforcement, aviation, marine, inspection, advertising and transportation applications.

The VMTR-21.5R is a 5-Wire Resistive Touch Screen. This model can be activated with nearly any type of device: exposed finger, glove, stylus, pointer, etc. Its immunity to surface contaminants (oil, water, dirt) makes it a popular choice for more challenging environments. It is a very cost-effective choice for public access, kiosks and more.

### Specifications

MODEL	VMTS-21.5D	VMTR-21.5C
LCD Panel	21.5" Color TFT LCD	
Touch Technology	SAW (Surface Acoustic Wave)	5-Wire Resistive
Touch Interface	USB	
Display Resolution	1920 x 1080 (1080p/60 Full HD)	
Viewable Area	18.76" x 10.55" (476.6 x 268.1 mm)	
Pixel Pitch	0.248mm	
Display Colors	16:7 M	
Aspect Ratio	16:9	
Brightness	250 nits	
Contrast Ratio	3,000:1	
Viewing Angle	178° (H) x 178° (V)	
Response Time	25 ms Trf	
Control	OSD (On-Screen Display) via Pushbuttons	
Video Input Connectors	VGA, HDMI, BNC	VGA, DVI
Video Inputs	VGA, HDMI, Composite BNC Input, Composite BNC Output	
Power Requirement	90-260 VAC	12 VDC/90-240 VAC
Power Consumption	25W	
Enclosure	Powder-Coated Steel	ABS
Mounting	100 x 100 mm VESA	
Operating Temperature/Humidity	14° to 122° F (-10 to 50° C); Humidity: 5-90% Non-Condensing	
Dimensions	19.51" (W) x 11.50" (H) x 0.72" (D) / 495.6 (W) x 292.2 (H) x 18.4 (D) mm	
Weight	6.4 lbs. / 2.9 kg	
Included Accessories	VGA and HDMI Cables	VGA & DVI Cables