



VMTW-15 Series

15" Waterproof Industrial Touch Screen Monitor

- 5-Wire Resistive Touch
- NEMA 4X Waterproof Stainless Steel Enclosure
- Resolution: 1024 x 768 (XGA)
- Video Inputs: VGA, DVI-D
- Lockable On-Screen Display (OSD) Controls
- Auto Re-Start After Power Loss
- **TRU-Tuff** Ensures Maximum Shock/Vibration Resistance
- 3 Year Warranty

The VMTRW-15C-24 waterproof touch screen monitors utilizes 5-wire resistive touch technology; the screen can be activated via a finger, gloved hand, credit card or stylus. The VMTRW-15C-24 features a rugged NEMA 4X waterproof stainless steel enclosure. They are ideal for wash-down environments in manufacturing or food processing. An extensive list of OEM options enables you to customize the VMTRW-15C-24 to meet your exact needs.

All TRU-Vu industrial LCD monitors are specifically designed for use in demanding applications. Every TRU-Vu monitor utilizes industrial-grade components and high-end LCD panels not found in retail/consumer-grade monitors. This ensures superior image quality, improved performance and greater durability. Our 3-Year Warranty ensures you of reliable worry-free operation. Visit www.TRU-VuMonitors.com for more details.

	Specifications
MODEL	VMTRW-15C-24
LCD Panel	15" Color LCD; LED Backlights
Touch Screen Type	5-Wire Resistive Touch
Touch Screen Interface	USB
Resolution	1024 x 768 (XGA)
Viewable Area	11.97 (W) x 8.98 (H) (304.128 x 228.096) mm)
Pixel Pitch	0.297 mm
Display Colors	16.7M
Aspect Ratio	4:3
Brightness	350 nits
Contrast Ratio	700:1
Viewing Angle	160° (H) x 150° (V)
Response Time	8 msec
Control	OSD (On-Screen Display) via Rear Panel Pushbuttons
Video Inputs	VGA & DVI
Power Requirement	12-24 VDC
Enclosure	Stainless Steel
Enclosure Rating	NEMA 4X Waterproof
Mounting	100 x 100 mm Rear VESA Mount Holes
Operating Temperature	+32° to +149° F (0° to +65° C)
Humidity	5-90% RH
Shock	50 G (20 msec, 1/2 sine)
Vibration	1.5 G (10-200 Hz P-P)
Dimensions	TBD
Included Accessories	DVI Cable, VGA Cable, Power Pigtail