



### VMXTRW-12C-SS

#### 12" Waterproof Industrial Touch Screen Monitor

- 5-Wire Resistive Touch
- NEMA 4X Waterproof Stainless Steel Enclosure
- Resolution: 1024 x 768
- Video Inputs: VGA, DVI-D
- Lockable On-Screen Display (OSD) Controls
- Auto Re-Start After Power Loss
- **TRU-Tuff** Ensures Maximum Shock/Vibration Resistance
- 3 Year Warranty

The VMTRW-12C-SS waterproof touch screen monitors utilize 5-wire resistive touch technology; the screen can be activated via a finger, gloved hand, credit card or stylus. The VMTRW-12C-SS features a rugged NEMA 4X waterproof stainless steel enclosure. They are ideal for wash-down environments in manufacturing or food processing or any other areas where liquids, steam or moisture may damage standard monitors. An extensive list of OEM options enables you to customize the VMTRW-12C-SS to meet your exact needs.

All TRU-Vu industrial LCD monitors are specifically designed for use in demanding applications. Every TRU-Vu monitor utilizes industrial-grade components and high-end LCD panels not found in retail/consumer-grade monitors. This ensures superior image quality, improved performance and greater durability. Our 3-Year Warranty ensures you of reliable worry-free operation. Visit [www.TRU-VuMonitors.com](http://www.TRU-VuMonitors.com) for more details.

	<b>Specifications</b>
<b>MODEL</b>	<b>VMTRW-12C-SS</b>
<b>LCD Panel</b>	12" Color LCD; LED Backlights
<b>Touch Screen Type</b>	5-Wire Resistive Touch
<b>Touch Screen Interface</b>	USB
<b>Resolution</b>	1024 x 768 (XGA)
<b>Viewable Area</b>	9.68 (W) x 7.27 (H) (245.76 x 184.32 mm)
<b>Pixel Pitch</b>	0.240 mm
<b>Display Colors</b>	16.7M
<b>Aspect Ratio</b>	4:3
<b>Brightness</b>	500 nits
<b>Contrast Ratio</b>	700:1
<b>Viewing Angle</b>	160° (H) x 150° (V)
<b>Response Time</b>	35 msec
<b>Control</b>	OSD (On-Screen Display) via Rear Panel Pushbuttons
<b>Video Inputs</b>	VGA & DVI-D
<b>Power Requirement</b>	90-240 VAC
<b>Enclosure</b>	Stainless Steel
<b>Enclosure Rating</b>	NEMA 4X Waterproof
<b>Mounting</b>	75 X 75 mm Rear VESA Mount Holes
<b>Operating Temperature</b>	-22° to +185° F (-30° to +85° C)
<b>Humidity</b>	5-90% RH
<b>Shock</b>	50 G (20 msec, 1/2 sine)
<b>Vibration</b>	1.5 G (10-200 Hz P-P)
<b>Dimensions</b>	TBD
<b>Included Accessories</b>	VGA Cable, Power Cable