



SRMXW-15.6R-24

15.6" Outdoor Sunlight Readable LCD Monitor

- 1,000 nits Brightness
- Full HD Resolution: 1920 x 1080 (1080p/60)
- NEMA 4X Water Resistant Stainless Steel Enclosure
- Video Inputs: VGA, HDMI, DisplayPort
- Anti-Reflective Glass
- Auto Re-Start After Power Loss
- **TRU-Tuff** Ensures Maximum Shock/Vibration Resistance
- Can Be Customized To Meet Your Needs
- 3-Year Warranty

The SRMXW-15.6R-24 is an outdoor Sunlight Readable monitor, designed to operate in direct sunlight, or other high ambient light conditions. This monitor produces over 1,000 nits of brightness, ensuring clear, sharp images even in direct, bright sunlight. The SRMXW-15.6R-24 features a rugged NEMA 4X stainless steel enclosure. It is completely sealed and will withstand rain, snow, sleet, etc. These are ideal for outdoor use in a wide range of applications including military, law enforcement, stadiums, amusement parks, advertising, transportation, marine, auto racing, oil and gas, inspection and other industries where viewability outdoors in direct sunlight is crucial.

All **TRU-Vu** industrial LCD monitors are specifically designed for use in demanding applications. Every **TRU-Vu** monitor utilizes industrial-grade components and high-end LCD panels not found in retail/consumer-grade monitors. This ensures superior image quality, improved performance and greater durability. Our 3-Year Warranty ensures you of reliable worry-free operation. Visit www.TRU-VuMonitors.com for more details.

	Specifications
MODEL	SRMXW-15.6R-24
LCD Panel	15.6" Color Panel; LED Backlights
Display Resolution	1920 x 1080 (1080p/60 Full HD)
Viewable Area	13.54" x 7.62" (344.16 x 193.59 mm)
Pixel Pitch	0.17925mm
Display Colors	262K
Aspect Ratio	16:9
Brightness	1,000 nits
Contrast Ratio	700:1
Viewing Angle	140° (H) x 120° (W)
Response Time	8 msec TrF
Control	OSD (On-Screen Display) via Pushbuttons
Video Inputs	VGA, HDMI, DisplayPort
Power Requirement	12-24VDC (Includes Locking Power Pigtail)
Power Consumption	25 Watts
Enclosure	NEMA 4X Weatherproof Stainless Steel
Mounting	100 x 100 mm Rear VESA Mount Holes
Operating Temperature	14° to 158° F (-10 to +70° C)
Shock	50G, Half-sine Wave, 20ms, X/Y/Z
Vibration	Acceleration: 1.5 G RMS; Random Wave; 10-200Hz; 30 mins Per Axis (X,Y,Z)
Dimensions	TBD
Weight	TBD
Warranty	3-Years