



### SRMXWP-15.6R

#### 15.6" Sunlight Readable Waterproof Panel-Mount Monitor

- Produce Clear, Sharp Images Even in Direct Bright Sunlight
- 1,000 Nits Brightness
- Aluminum Panel-Mount Enclosure
- NEMA 4X / IP65 Waterproof Front Face
- Resolution: 1920 x 1080
- Ambient Light Sensor to Adjust Screen Brightness Automatically
- Auto Re-Start After Power Loss

The SRMXWP-15.6R Sunlight Readable waterproof panel-mount monitors are designed to operate in direct bright sunlight, or in other high ambient-light conditions. They utilize state-of-the-art LED backlights to produce 1,000 nits of brightness (vs. 250-300 nits for standard monitors). They are ideal for wash-down environments or where liquids, steam or moisture may damage standard monitors. The SRMXWP-15.6R is perfect for use in a wide range of industrial, marine, military, manufacturing, inspection, advertising and transportation applications where viewability in direct, bright sunlight is crucial.

All TRU-Vu industrial LCD monitors are specifically designed for use in demanding applications. Every TRU-Vu monitor utilizes industrial-grade components and high-end LCD panels not found in retail/consumer-grade monitors. This ensures superior image quality, improved performance and greater durability. Our 3-Year Warranty ensures you of reliable worry-free operation. Visit [www.TRU-VuMonitors.com](http://www.TRU-VuMonitors.com) for more details.

Specifications	
<b>MODEL</b>	<b>SRMXWP-15.6R</b>
<b>LCD Panel</b>	15.6" Color TN Panel (LED Backlights)
<b>Resolution</b>	1920 x 1080 (XGA)
<b>Viewable Area</b>	13.55" (W) x 7.62" (H) (344.16 x 193.59 mm)
<b>Pixel Pitch</b>	0.17925mm
<b>Display Colors</b>	16.7 M
<b>Aspect Ratio</b>	16:9
<b>Brightness</b>	1,000 nits
<b>Contrast Ratio</b>	700:1
<b>Viewing Angle</b>	160° (H) x 140° (W)
<b>Response Time</b>	8 msec Trf
<b>Control</b>	OSD (On-Screen Display) via Pushbuttons
<b>Video Inputs</b>	VGA, HDMI, DisplayPort
<b>Power Requirement</b>	12-24 VDC
<b>Power Consumption</b>	TBD
<b>Enclosure</b>	Panel Mount with NEMA 4X Aluminum Front Galvanized Steel Rear
<b>Enclosure Rating</b>	NEMA 4X / IP65
<b>Operating Temperature</b>	14° to 158° F (-10 to 70° C)
<b>Shock/Vibration</b>	120 G (20 msec, ½ sine) / 1.0 G RMS 10-3
<b>Dimensions</b>	TBD
<b>Warranty</b>	3 Years