



### SRMH-15-AR Series

#### 15" Sunlight Readable Monitors

- Produces Clear, Sharp Images Even in Direct Bright Sunlight
- 1,500 nits Brightness
- Anti-Reflective Coating
- Dim-to-Black Function For Night-Time Use
- Auto Re-Start After Power Loss
- **TRU-Tuff** Treatment Ensures Maximum Shock & Vibration Resistance

The SRMH-15-AR Series Sunlight Readable LCD monitors are designed to operate in direct bright sunlight, or in other high ambient-light conditions. They utilize state-of-the-art LED backlights to produce over 1,700 nits of brightness (vs. 250-300 nits for standard monitors). This results in amazingly bright, crystal-clear images, even with direct, bright sunlight on the face of the screen. The SRMH-15-AR Series Sunlight Readable monitors are ideal for use in a wide range of industrial, law enforcement, aviation, marine, military, inspection, advertising, material handling (cranes) and transportation applications where viewability in direct bright sunlight is crucial.

All TRU-Vu industrial LCD monitors are specifically designed for use in demanding applications. Every TRU-Vu monitor utilizes industrial-grade components and high-end LCD panels not found in retail/consumer-grade monitors. This ensures superior image quality, improved performance and greater durability.


Specifications		
MODEL	SRMH-15S-AR	SRMH-15S-AR-24
LCD Panel	15" Color LCD; LED Backlights	
Resolution	1024 x 768 (XGA)	
Viewable Area	11.97"(W) x 8.98"(H) (304.12 x 228.09 mm)	
Pixel Pitch	0.297mm x 0.297mm	
Display Colors	16.2 M	
Aspect Ratio	4:3	
Brightness	1,500 nits	
Contrast Ratio	700:1	
Viewing Angle	170° (H) x 160° (V)	
Response Time	8 msec Trf	
Control	OSD (On-Screen Display) via Front Panel Pushbuttons	
Video Inputs	VGA, S-Video, Composite (BNC) NTSC/PAL Auto-Recognition	
Audio	Optional	Rear Speaker
Power Requirement	12 VDC (2.1mm Barrel Plug) 90-240 VAC via Included Power Brick	12-24 VDC (2.1mm Barrel Plug)
Power Consumption	50 Watts	
Enclosure	ABS	
Mounting	Via Included Tabletop Base or Via 75x75mm Rear VESA Mount Holes	
Operating Temperature	-4° to +149°F (-20° to +65° C)	
Humidity	5-90% RH	
Shock	50 G (20 msec, 1 / 2 sine)	
Vibration	1.5G RMS 10-200 HZ	
Dimensions	13.66"(W) x 10.9"(H) x 1.78"(D) (347 x 276 x 45.20 mm)	
Weight	4.87 lbs. (2.21 kg)	5.09 lbs. (2.3 kg)
Warranty	3 Years	

## SRMH-15-AR Series

### 15" Sunlight Readable LCD Monitors

#### Dimensions:

UNIT : mm



#### Standard Accessories:

- 90-240 VAC Power Brick 9 (Except "-24" Model)
- VGA Cable
- Tabletop Base
- 12-240 Pigtail (-24 Model Only)
- Audio Cable (-24 Model Only)

#### Available Options:

- DVI Video Input
- Internal Speakers
- HDMI Input
- Protective Anti-Reflective Glass
- Automated Ambient Light Sensor
- Panel Mount
- Open-Frame Configuration
- Private Label
- Other Customer - Specific Modifications