

MMZBTP-21.5G-X Series

21.5" Medical Touch Screen Monitor

- 21.5" Medical Touch Screen Monitor
- Projected Capacitive Touch Screen (P-Cap)
- Meets UL 60601-1 Ver. 3.1; IEC 60601-1-2 4th Edition
- 1920 x 1080 Full HD Resolution
- White or Black ABS Enclosure; Bezel-Less Front Simplifies Cleaning, Improves Safety & Hygiene
- Built-In Speakers
- Auto Re-Start After Power Loss
- Compatible with Automation Direct HMI
- Optional Rear Input Compartment Cover for Built-in Cable Management
- 3-Year Warranty
- TAA Compliant



The TRU-Vu MMZBTP-21.5G-X Series are 21.5" medical touch screen monitor. It conforms to UL 60601-1 Edition 3.1, and IEC 60601-1-2 4th Edition. Our 21.5" medical-grade touch screen is ideal for hospital operating rooms, medical carts, medical imaging systems, fluoroscopy, endoscopy, OEM medical systems, PACS and other medical applications. The MMZBTP-21.5G-XB model is also compatible with Automation Direct HMI.

MEDICAL TOUCH SCREEN, OPTICAL IMAGE QUALITY

Our widescreen 21.5" medical touch screen monitor provides 1080p, 1920 x 1080 Full HD resolution. The super-wide 178 x 178 viewing angles ensure clear, sharp images when viewed from nearly any angle. Thanks to its high resolution, brightness and high contrast ratio, our 21.5" medical-grade touch screen provides razor-sharp, flicker free images. This enables doctors and surgeons to make accurate, and timely, critical decisions. Fast response time and lag-free transmission of images ensure the most detailed images in the OR today.

21.5" MEDICAL-GRADE P-CAP TOUCH SCREEN

The projected capacitive touch technology enables multi-touch, with up to 10 simultaneous touch points. The P-Cap touch screen can be activated via exposed fingers, or with a surgical glove. The screen is unaffected by dirt, grease or moisture on the glass surface. To help you guide you through the advantages of the 5 most common types of touch technology, see our tutorial on [touch screen basics](#). Our convenient [touch screen comparison chart](#) will provide a quick overview of advantages and disadvantages of each type.

MEDICAL BEZEL-LESS MONITOR, FULLY FLAT DESIGN

Our zero-bezel ABS enclosure features a single pane of glass across the entire front face of its 21.5" medical-grade touch screen. Due to the absence of any raised-edge bezel (frame) around the front edges, this touch screen is extremely easy to clean (see [Cleaning Instructions Guide](#)) and improves overall hygiene. The bezel-less monitor enclosure eliminates the build-up of germs and contamination, as there is no bezel for them to reside beneath, as with standard enclosures. The rounded corners of the housing add a measure of comfort and safety, as well as improved aesthetics. Available in Black or White Zero-Bezel Enclosure.

This lightweight surgical display features rear VESA mount holes which enables easy mounting via spring arms, surgical booms or tabletop stands. Visit our wide range of [LCD monitor mounts and stands](#) to complete your installation. Rear speakers are standard and can provide useful tones or alarms.

FAN-LESS MEDICAL GRADE DISPLAY

All our Medical displays are built without internal fans. A fanless design provides numerous important benefits. Reliability and durability are greatly increased, since one major moving part, the fan, which is subject to mechanical failure, is eliminated. A fan-less design also provides a higher level of safety in sterile environments. It eliminates the circulation of pathogens and dust. Lastly, a fan-less monitor is also quieter.

OUR EXPERT TECHNICIANS WILL HELP YOU SELECT THE BEST MEDICAL TOUCH SCREEN SOLUTION

With over 200 LCD monitors and touch screens on our site, selecting the ideal medical monitor solution may be a bit overwhelming. To help narrow-down the choices, check out our [Advanced Search Tool](#). For example, this enables you to filter by your own useful features. View all **Medical-Grade** displays only. Shop by size **21.5" to 65"** monitors, see our full line of **Touch Screen Monitors**, filter by standard brightness, or see all **bezel less** monitors. Custom OEM LCD Displays and Private Label Monitors are also an option if you have very specific requirements.

Remember, our team members are ready to help! We can determine the exact medical touch screen solution that will meet your specific needs. TRU-Vu medical displays will help provide crystal-clear images for your medical projects. Call (847) 259-2344 today to speak with one of our medical monitor specialists. Above all, we will listen. It's one of the things we do best. Our professional advisors will ensure the medical monitor or touch screen you receive will be everything you had hoped it would for your medical imaging system.

If you prefer, fill out a quick form with your requirements, and our specialists will guide you to the proper models that will work best.

All **TRU-Vu Medical Grade** monitors utilizes industrial-grade components and high-end LCD panels. These are not found in retail or consumer-grade monitors. Therefore, this ensures superior image quality, improved performance and greater durability.


SPECIFICATIONS

	MMZBTP-21.5G-X	MMZBTP-21.5G-XB
LCD Panel	21.5" Color AHVA; LED Backlights	
Touch Screen Type	Projected Capacitive, 10 Simultaneous Touch Points, Anti Glare Glass	
Touch Interface	USB	
Resolution	1920 x 1080 (FullHD)	
Viewable Area	18.76" W x 10.55" H (476.6 x 268.1 mm)	
Pixel Pitch	0.248mm	
Display Colors	16.7M	
Aspect Ratio	16:9	
Brightness	350 nits	
Contrast Ratio	1,000:1	
Viewing Angle	178° (H) x 178° (V)	
Response Time	22 msec Trf	
Control	OSD (On-Screen Display) via Capacitive Buttons Under Front Edge	
Video Inputs	DVI-D, HDMI, DisplayPort	
Audio	Dual Rear Speakers	
Power Requirement	100-240 VAC via included Medical-Grade External Power Supply with Locking Connector; Includes Green Dot Power Cord	
Power Consumption	16.8W	
Enclosure	Zero-Bezel Front; White ABS Rear	Zero-Bezel Front; Black ABS Rear
Enclosure IP Rating	Front: IP65 Rear: IP30	

	MMZBTP-21.5G-X	MMZBTP-21.5G-XB
Mounting	100mm x 100mm Rear VESA Holes; Optional Tabletop Base	
Operating Temperature	32° to 122° F (0° x 50° C)	
Humidity	5-90% RH	
Shock / Vibration	50G Half-sine 20 msec ; 1.5G 10-200 Hz	
Certifications	UL: ANSI/AAMI ES60601-1 (2005/(R)2012 + A1:2012, C1:2009/(R)2012 + A2:2010/(R)2012) CAN/CSAC22.2 No. 60601-1:14 CB : IEC 60601-1-6:2010/AMD1:2013, IEC 60601-1-6:2010, IEC 60601-1:2005/AMD1:2012, IEC 60601-1:2005	
Dimensions	20.72" (W) x 12.65" (H) x 2.25" (D) (526.2 x 321.2 x 57.1 mm)	
Weight	10.2 lbs (4.62 kg)	
Warranty	3 Years	

Note: Specifications subject to change without notice.

DIMENSIONS (MM)



UNLESS OTHERWISE SPECIFIED	
LENGTH	TOLERANCE
0-6	±0.10
7-30	±0.20
31-100	±0.30
101-300	±0.50
301-UP	±0.70
ANGLE	±1.0°

MMZBTP-21.5G-XB

Standard Accessories:

- External Medical-Grade Power Supply
- Hospital-Grade Green Dot Power Cord
- DVI Cable
- Audio Cable
- USB Cable
- Ground Wire

Available Options:

- Tabletop Base
- Optional Rear Input Compartment Cover (ACC-MMZB-21.5-COV)
- Black Enclosure
- Wall Mount Brackets
- DICOM Part 14 GSDF Calibration
- Private Label
- Other Customer-Specific Modifications