


## VMM-19U-24S

### Rugged 19 inch Monitor

- 19" Industrial-Grade LCD Monitor
- 4:3 / 5:4 Aspect Ratio
- 250 nits Brightness
- *TRU-Tuff* Treatment Ensures Maximum Shock & Vibration Resistance
- Auto Re-Start After Power Loss
- Lockable On-Screen Display Controls
- Can Be Customized to Meet Your Needs
- 3-Year Warranty



## 19 INCH MONITOR WITH 5:4 / 4:3 ASPECT RATIO

The VMM-19U-24S are industrial 19 inch monitors. They offer 1280 x 1024 resolution and a 5:4 aspect ratio. They are ideal for use with analog cameras, and BNC cameras. Likewise, many legacy machine vision systems benefit. Furthermore, we build them with true industrial-grade components for long-term reliability. For example, they receive our exclusive TRU-Tuff treatment. Moreover, the TRU-Tuff process includes RTV silicone on all connections and critical components. Additionally, all wires are dressed, tie-wrapped and secured. Lastly, we apply ThreadLock to all screws to ensure they remain secured. This results in a rugged, dependable monitor you can rely on. The VMM-19U-24S can operate on 12VDC, 24VDC, or 90-240VAC via the included external AC power supply.

### RUGGED 19" DISPLAYS BUILT FOR DEMANDING APPLICATIONS

The VMM-19U-24S also provides a 250 nits brightness. The result is crisp, vibrant video images. *TRU-Vu* industrial LCD monitors are specifically designed for use in demanding industrial, commercial, and A/V applications. For instance, every *TRU-Vu* monitor utilizes industrial-grade components and high-end LCD panels not found in retail or consumer-grade monitors. This ensures superior image quality, improved performance and greater durability.

The VMM-19 Series industrial 19" LCD monitors offer a variety of video inputs and are available in standard, open frame, rack mount, panel mount, NEMA/IP waterproof, and touch screen configurations. An extensive list of available OEM options enables you to customize a solution to your specific needs.

### 19 INCH MONITORS DEPLOYED WORLDWIDE

The VMM-19U-24S 19 inch monitors have a 5:4 (aka 4:3) aspect ratio are deployed in many industries and applications. This includes manufacturing plants, machine vision inspection systems, and food and beverage plants. They are also found in surveillance systems, specialty vehicles, museums and pipeline inspection systems.

TRU-Vu monitors are backed by our full 3-year warranty. Consequently, this ensures you of many years of reliable service.

### OUR TECHNICAL EXPERTS ARE READY TO HELP YOU FIND THE BEST 19" LCD MONITOR

With over 200 LCD monitors and touch screens on our site, selecting the ideal equipment, or touch screen solution may be a bit overwhelming. To help narrow down the choices, check out our [Advanced Search Tool](#). For example, this enables you to filter by your own specific search requirements. See our full line of standard brightness monitors and 13.3" to 19" monitors for similar models to the VMM-19 Series. They can also be private-labeled with your company name and/or logo on the front

bezel.

Finally, our team members are ready to help! We can determine the exact solution that will meet your specific needs . Certainly, TRU-Vu will help provide clear images for your operating requirements . Call **(847) 259-2344** today to speak with one of our specialists. Above all, we will listen. It's one of the things we do best. Our professional advisors will ensure the monitor or touch screen you receive will be and do everything you had hoped it would!

If you prefer, fill out a quick form with your requirements, and we will guide you to the proper models that will work best.


To see technical information, tips, tricks and guides to LCD monitors and technology, visit our **TECH CENTER**.

## SPECIFICATIONS

	<b>VMM-19U-24S</b>
LCD Panel	19" Color Defect-Free LCD; LED Backlights
Display Resolution	1280 x 1024 (SXGA)
Viewable Area	14.81" (W) x 11.85" (H) (376.17 x 300.98 mm)
Pixel Pitch	0.294mm x 0.294mm
Display Colors	16.7 Million
Aspect Ratio	4:3 (5:4)
Brightness	250 nits
Contrast Ratio	1000:1
Viewing Angle	170° (H) x 160° (V)
Response Time	5 msec Trf
Control	OSD (On-Screen Display) via Front Panel Pushbuttons
Video Inputs	VGA, HDMI, BNC Loop-Thru, NTSC/ PAL Auto- Recognition
In/Output Impedance	75Ω / Auto Terminating Output
Audio	Rear Speakers
Power Requirement	12 VDC (2.1 mm Barrel Plug); 24VDC (2.5mm Barrel Plug); & 90-240 VAC via Included Power Brick
Power Consumption	18 Watts
Enclosure	ABS
Mounting	75 x 75mm Rear VESA Mount Holes
Operating Temperature	32° to 122° F (0° to 50° C)
Operating Altitude	To 18,000 Ft.
Humidity	5-90% RH
Shock	50 G (20 msec, 1/2 sine)
Vibration	1.5G RMS 10-200 HZ
Dimensions	16.59" (W) x 13.79" (H) x 1.85" (D) (421.40 x 350.50 x 47.1 mm)
Weight	8 lbs. (3.62 kg)
Warranty	3-Years

Note: Specifications subject to change without notice.

## DIMENSIONS (MM)



**Standard Accessories:**

- 90-240 VAC Power Brick
- VGA Cable
- Audio Cable
- Power Pigtail

**Available Options:**

- Tabletop Stand (TTB-27)
- -22°F to +185°F Operating Temperature
- 100-240VAC Power Adaptor (PS-12)
- DVI, HD-SDI, or DisplayPort
- 1,000 Nits Brightness
- Optical Bonding
- Panel Mount Enclosure
- Anti-Reflective or Vandal-Resistant Glass
- Steel Enclosure
- NEMA 4X Waterproof Stainless Steel Enclosure
- Touch Screen (VMTC-19C)
- Rack Mount Bracket MB-Rack-19
- Open-Frame Configuration
- Private-Label