

VMTRWP-15R-24

15" Waterproof Panel-Mount Touch Screen Monitor

- 5-Wire Resistive or P-Cap Touch
- Stainless Steel Panel-Mount Enclosure
- NEMA 4X Waterproof Front
- Lockable On-Screen Display (OSD) Controls
- Auto Re-Start After Power Loss
- *TRU-Tuff* Ensures Maximum Shock/Vibration Resistance
- 3-Year Warranty



15" WATERPROOF PANEL MOUNT TOUCHSCREEN

The VMTRWP-15R-24 is a 15" [waterproof panel-mount touchscreen](#). The 5-wire resistive touch screen can be activated by almost any object. For example; gloved finger, stylus, pen, etc. This model is ideal for wash-down environments or where liquids, steam or moisture may damage standard monitors.



The VMTRWP-15R-24 15" waterproof touch screen feature a stainless steel panel mount enclosure. The front face is NEMA 4X waterproof. This enables it to be used in any wet environment, in manufacturing plants, outdoors or at sea. With extreme operating temperature ranges from -22° to +185° F, this 15" waterproof touch screen can be used nearly anywhere. There's also a handy guide on how to [install a monitor or touchscreen into wall or cabinet](#).

The VMTRWP-15R-24 Series 15" waterproof panel-mount touchscreen is perfect for use in a wide range of [industrial](#), [military](#), and [manufacturing](#) applications. [Automated inspection](#), [kiosks](#) and [transportation](#) applications will also benefit.

Additionally, see our full line-up of industrial-grade [Sunlight Readable and Daylight Readable](#). This highlights all of our high brightness monitors. Also, you'll find the sunlight readable touch screens in all the sizes and configurations available.

DESIGNED FOR DEMANDING APPLICATIONS

All TRU-Vu industrial LCD monitors are specifically designed for use in demanding applications. Every TRU-Vu monitor utilizes industrial-grade components and high-end LCD panels. They are not found in retail/consumer-grade monitors. This ensures superior image quality, as well as improved performance and greater durability. Our 3-Year Warranty ensures you of reliable worry-free operation.

OUR TECHNICAL EXPERTS ARE READY TO HELP YOU FIND THE RIGHT DISPLAY

With over 540 LCD monitors and touch screens on our site, selecting the ideal equipment, or touch screen solution may be a bit overwhelming. To help narrow-down the choices, check out our [Advanced Search Tool](#). For example, this enables you filter by your own specific search requirements.

Finally, our team members are ready to help! We can determine the exact solution that will meet your specific needs . Certainly, TRU-Vu will help provide crystal-clear images for your operating requirements . Call [\(847\) 259-2344](tel:847-259-2344) today to speak with one of our specialists. Above all, we will listen. It's one of the things we do best. Our professional advisors will ensure the monitor or touch screen you receive will be everything you had hoped it would!

If you prefer, fill out a [quick form](#) with your requirements. We will guide you to the proper models that will work best once we better understand your needs.

SPECIFICATIONS

	VMTRWP-15R-24
LCD Panel	15" Color TN LCD Panel (LED Backlights)
Touch Technology	5-Wire Resistive Touch
Touch Interface	USB
Resolution	1024 x 768 (XGA)
Viewable Area	11.97" (W) x 8.98" (H) (304.12 x 228.09 mm)
Pixel Pitch	0.297mm
Display Colors	16.2 M
Aspect Ratio	4:3
Brightness	350 nits
Contrast Ratio	700:1
Response Time	8 msec Trf
Viewing Angle	160° (H) x 150° (W)
Control	OSD (On-Screen Display) via Rear Panel Pushbuttons
Video Inputs	VGA, HDMI, DisplayPort
Power Requirement	12-24VDC (2.5mm Barrel Plug)
Enclosure	Stainless Steel Panel-Mount (Rear Clamp) 75x75mm Rear VESA Holes
Operating Temp.	-22° to 185°F (-30° to +85°C)
Humidity	8-90%RH
Shock	50 G (20 msec, ½ sine)
Vibration	1.5G RMS 10-200 HZ
Dimensions	Approx. 15.98" (W) x 12.39" (H) (405.80 x 314.60 mm)
Warranty	3 Years

Note: Specifications subject to change without notice.